



Reliable, responsive,  
and recognized since 1994.

**CORPORATE HEADQUARTERS**

114 Lincoln Ave.  
Cobleskill, NY 12043  
888-680-7974  
www.firetesting.com

## PRODUCT LISTING

**Reference No.** CS-A-1162-20min

**Status:** Current

**Manufacturer:**

Construction Specialties Inc  
Acrovyn Door System, Building #3  
6696 Route 405, Muncy, PA 17756

**Product(s):**

Acrovyn 20 min. Positive Pressure, Category A, Fire-Rated Door with Acrovyn 4000 faces and Acrovyn patented replaceable wood or engineered (SCL) stiles and Acrovyn or Stainless Steel edges, for use in listed steel frames.

**Report:**

Acrovyn 20 min. Positive Pressure, Category A, Fire-Rated Door with Acrovyn 4000 faces and Acrovyn patented replaceable wood or engineered (SCL) stiles and Acrovyn or Stainless Steel edges, for use in listed steel frames:

- Bonded Particleboard Core
- Bonded FSC Particleboard Core
- Bonded Agrifiber Core
- Bonded SCL Core
- Lead Lined with Bonded FSC Particleboard Core
- Lead Lined with Bonded Particleboard Core
- Lead Lined with Bonded SCL Core

Models: Flush, Dutch, Transom Panel, Barrier Resistant (Wicket), and Recessed Panel\*

\*Note: Maximum recessed panel depth 3/8", no limit to design or pattern.

Single Swing: 5'-0" x 10'-0", Intumescent applied to the full width of the top rail only.

Standard Pairs and Double Egress: 10'-0" x 10'-0", Intumescent applied to the full width of the top rail and the meeting edge stiles, concealed behind the replaceable edge cover.

Standard Pairs require 3 point latching and Double Egress require 4 point latching.

Optional construction is available for 2 point latching for Pairs and Double Egress configurations.

Approved for any listed and labeled glazing for up to 2820 sq inches of visible glass, with metal\* or wood bead lite kits.

\*Note: Includes wood veneer and Acrovyn wrapped metal lite kits.



Reliable, responsive,  
and recognized since 1994.

**CORPORATE HEADQUARTERS**

114 Lincoln Ave.  
Cobleskill, NY 12043  
888-680-7974  
[www.firetesting.com](http://www.firetesting.com)

**PRODUCT LISTING**

Attribute Value

CSI Code 08 10 00 Doors and Frames

CSI Code 08 14 00 Wood Doors

Single Swing, Pairs, and Double Egress

Standards Tested To:

UL 10C, NFPA 252, ASTM E-2226 [UBC 7-2, and CAN4 S104 contain the criteria which is in UL 10C.]

Listing Category A doors: "No additional edge sealing system required for fire rating."

Guardian Test Reports:

GL 116811, 2/9/2012

Engineering Evaluation Reports:

EER 50612, 8/13/12 rev 1/10/13; EER 57613, 7/30/13; EER 69913-1, 9/18/13; EER 69913-2, 9/18/13